

Uno & Duo Booster

Heavy-duty, Cold-water, Stationary, Electric-driven High-pressure Washers

www.nilfisk-alto.us



**Nilfisk
ALTO**

Uno & Duo Booster



Durability

KEW's Uno and Duo Boosters are built to handle the toughest cleaning tasks. Whether you have a single-user application (Uno) or dual-user cleaning requirements (Duo), the Uno and Duo Boosters are designed to operate more than 8 hours a day. A heavy-duty, stainless-steel cabinet and chassis ensures additional longevity and makes the units easy to clean. Made for high-hygiene applications, the Uno and Duo Boosters are ideal for use in the food and beverage industry, pharmaceutical industry, meat processing plants, and much more.



Reliability

The Uno and Duo Boosters come equipped with the renowned KEW C3 pump with 4 ceramic pistons and a low-speed 1750-RPM Totally Enclosed Fan Cooled (TEFC) motor. In addition, the C3 pump allows the use of preheated water of up to 160°F enabling these cold-water units to run hot water for degreasing tasks. Over the last 20 years the C3 pump has proven itself to be the most reliable and durable pump on the market, designed to tackle heavy-duty cleaning applications, day after day.

User-Friendly and Servicability

Besides being a workhorse, the Uno and Duo comes with a load of features making them easy to use and service:

- Visible oil level detector
- Easy-to-use start/stop button
- Low water security function
- Stainless-steel valves
- Brass cylinder head
- Closed oil system
- Integrated flow sensor for dry-run protection
- Pump head with integrated filter
- Powerful integrated motor with dual thermal sensors
- Integrated LCD control for easy troubleshooting
- Automatic start/stop function



Uno & Duo Booster Specifications

MODEL	Uno Booster	Uno Booster	Duo Booster	Duo Booster
Part Number	107340123 (1x220V)	107340122 (3x220V) 107340124 (3x440V)	107340324 (1x220V)	107340322 (3x220V) 107340323 (3x440V)
System Volume (GPM)	5.0	5.5	5.0 - 10.0	5.5 - 11.0
Pressure (PSI)	2200	2600	2200	2600
Max Inlet Temp	160°F	160°F	160°F	160°F
Motor (HP)	7.3	8.8	2 x 7.3	2 x 8.8
Auto Start/Stop	Yes	Yes	Yes	Yes
Hour Meters	Yes for each pump	Yes for each pump	Yes for each pump	Yes for each pump
Voltage	1 x 220	3 x 220 & 3 x 460	1 x 220	3 x 220 & 3 x 460
Amperage	29	24 & 12	58	24 & 12
Dimensions (LxWxH)	28 X 16 X 28	28 X 16 X 28	28 x 16 x 39.5	28 x 16 x 39.5
Weight (lbs)	179	179	353	353

Versatility

KEW offers an extensive line of accessories to compliment our industrial pressure washers. Knowledgeable, KEW-trained field engineers from over 100 local stocking distributors provide on-site applications expertise and prompt local service, nationwide. For more information, contact your local KEW distributors.

DISTRIBUTED BY:

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>