

Sentry Switched CDU

Key Features

- > **Remote Power Management:** Power cycle individual power outlets, or groups of power outlets, to remotely reboot servers and network devices, anywhere in the world. Or, power-off unused power receptacles
- > **High Power Distribution:** 3-Phase power; 20 or 30-Amp power input feed options
- > **High Density:** Single power input feed; 24 outlets per enclosure
- > **IP Access & Security:** Web interface, SSL, SSH, Telnet, SNMP, FTP, SNTp, Syslog, LDAP, LDAPS, TACACS and RS-232 access
- > **Add an Expansion Module:** Daisy chain the Switched CDU Expansion Module (CW/CX) for power management of separate power circuits from a single IP address
- > **Environmental Monitoring:** Each Switched CDU supports two temperature & humidity probes and reports conditions thru the Web interface
- > **Enterprise View:** View and access multiple Switched CDUs from one Web interface**
- > **SNMP Traps:** Provide automated alerts for power and environmental conditions
- > **Input Current Monitor:** Precisely measure the aggregate current draw (in amps) on each power circuit. On-site verification of the input current with the LED digital display. Remote verification via browser or serial screen.
- > **Power-up Sequencing:** Prevent an in-rush power overload

CW-24VD/Y

High-Density Power Distribution

The Switched CDU's combine remote configuration and management with power distribution and power and environmental monitoring. Reboot a single or dual-power server with one command. Receive SNMP-based alerts and email alerts when power or environmental conditions exceed thresholds. Assign users specific access rights to designated outlets or groups.

Only the Switched CDU products provide the flexibility needed for all data centers and remote sites, including power requirements for high-amp, high voltage; UL 60950-1 branch circuit protection; SSL & SSH security; and SNMP-based input current monitoring.

The Switched CDU also supports Enterprise View PDU Manager. This gives the engineer the ability to manage a large installation of Networked CDUs from one location, view and access multiple Smart and Switched CDUs from a single web interface.

Additional Benefits:



Branch Circuit Protection

The Sentry CDU Family meets the new UL 60950-1 requirement for branch circuit protection.

Attention! The Sentry CDU products meet the above criteria by providing overcurrent protection with UL-listed Bussman SC fuses for each branch circuit.



Input Current Monitoring

The CDU's exclusive True RMS current monitoring is critical to preventing overloads in high-density computing environments. LED digital displays on the CDU enclosure report the input current of each phase or branch circuit.



Temperature and Humidity

The Switched CDU supports two external probes. Each of these probes measure both temperature and humidity. Receive SNMP-based alert notifications when conditions exceed defined thresholds.



Model	Available Input Voltages	Amperage	Available Input Cord	Outlets	Dimensions** (L x W x D)
CW-24VD-L20M	3-Phase Delta, 208V 50/60Hz	20A	NEMA L15-20P Cordset	(24) IEC 60320/C13	69.0" x 1.75" x 2.25"
CW-24VD-L30M	3-Phase Delta, 208V 50/60Hz	30A	NEMA L15-30P Cordset	(24) IEC 60320/C13	69.0" x 1.75" x 2.25"
CW-24VY-L20M*	3-Phase Wye, 208V 50/60Hz	20A	NEMA L21-20P Cordset	(24) IEC 60320/C13*	69.0" x 1.75" x 2.25"
CW-24VY-L30M*	3-Phase Wye, 208V 50/60Hz	30A	NEMA L21-30P Cordset	(24) IEC 60320/C13*	69.0" x 1.75" x 2.25"

*This unit has an additional NEMA 5-20R, 110V Utility Outlet

**Please note that the depth of these enclosures are 3.0" deep at the placement of the fuse retractors

Additional Features and Specifications

Agency Approvals

- > US & Canada (cTUVus mark) to UL 60950-1:2003 and CAN/CSA 22.2 No. 60950-1-03
- > European Union (TUVGS mark) to EN 60950-1:2001
- > FCC Class A, Part 15
- > CE
- > EMC - EN 55022 Class A, EN 55024

Communications and Security

- > 10/100 BaseT Ethernet
- > HTTP/HTTPS
- > SSLv3/TLSv1
- > SNMPv2
- > SSHv2
- > Telnet
- > LDAPv3
- > LDAPS
- > TACACS+
- > RS-232 (Serial)

Branch Circuit Protection

- > Compliant to UL 60950-1

Power Cord Options

- > PTCORD-1 IEC 60320/C19 - NEMA L6-20P , 10'
- > PTCORD-2 IEC 60320/C19 - Schuko 10'
- > PTCORD-3 IEC 60320/C19 - IEC 60309 (BS4343, CEE17) 16/20A Blue (UK Commando) 10'
- > PTCORD-4 IEC 60320/C19 - BS1363 13A (UK) 10'
- > PT-ADP-C19 Cable mount IEC 60320/C19 Connector

Accessories

- > Optional Temperature & Humidity Probe
EMTH-1-1 Temperature & Humidity Probe, 10'

**Enterprise View sold separately



Expansion Module

Model Numbers

- > CX-24VD-L20M
- > CX-24VD-L30M
- > CX-24VY-L20M
- > CX-24VY-L30M



Server Technology

EMEA	NORTH AMERICA / ASIA
Server Technology Intl	Server Technology, Inc.
Sienna Court	1040 Sandhill Drive
The Broadway	Reno, NV 89521
Maidenhead	United States
Berkshire	1.775.284.2000 Tel
SL6 1NJ	1.775.284.2065 Fax
United Kingdom	sales@servertech.com
+44 (0) 1628 509053 Tel	www.servertech.com
+44 (0) 1628 509100 Fax	www.servertechblog.com
salesintl@servertech.com	

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>